



Bearing NO.	Dimensions (mm / in.)									Dynamic load ratings(N)	Static load ratings(N)	Weight (kg)
	d1	d	D	B	C	B1	B2	ds	F			
FJ-UK205;H2305	20	25	52	23	17	35	8	38	4.3	14000	7850	0.24
205;HE2305	3/4	0.9843	2.0472	0.9055	0.6693	1.378	0.315	1.496	0.169			
FJ-UK206;H2306	25	30	62	26	19	38	8	45	5.2	19450	11250	0.36
206;HE2306	1	1.1811	2.4409	1.0236	0.7480	1.496	0.315	1.772	0.204			
206;HS2306	7/8											
FJ-UK207;H2307	30	35	72	29	20	43	9	52	5.7	25700	15200	0.52
207;HS2307	1-1/8	1.3780	2.8346	1.1417	0.7874	1.693	0.354	2.047	0.224			
FJ-UK208;H2308	35	40	80	31	21	46	10	58	6.2	29500	18100	0.67
208;HE2308	1-1/4	1.5748	3.1496	1.2205	0.8268	1.811	0.394	2.283	0.244			
208;HS2308	1-3/8											
FJ-UK209;H2309	40	45	85	31	22	50	11	65	6.6	32700	20900	0.77
209;HA2309	1-7/16	1.7717	3.3465	1.2205	0.8661	1.969	0.433	2.559	0.26			
209;HE2309	1-1/2											
209;HS2309	1-5/8											
FJ-UK210;H2310	45	50	90	32	24	55	12	70	6.5	35000	23200	0.92
210;HA2310	1-11/16	1.9685	3.5433	1.2598	0.9449	2.165	0.472	2.756	0.256			
210;HE2310	1-3/4											
210;HS2310	1-5/8											
FJ-UK211;H2311	50	55	100	35	25	59	12	75	7.1	43300	29200	1.15
211;HA2311	1-15/16	2.1654	3.937	1.378	0.9843	2.323	0.472	2.953	0.28			
211;HE2311	2											
211;HS2311	1-7/8											
FJ-UK212;H2312	55	60	110	38	27	62	13	80	7.9	47700	32800	1.47
212;HS2312	2-1/8	2.3622	4.3307	1.4961	1.0630	2.441	0.512	3.15	0.311			
FJ-UK213;H2313	60	65	120	40	28	65	14	85	8	57200	40000	1.81
213;HA2313	2-3/16	2.5591	4.7244	1.5748	1.1024	2.559	0.551	3.346	0.315			
213;HE2313	2-1/4											
213;HS2313	2-3/8											
FJ-UK215;H2315	65	75	130	44	30	73	15	98	8.6	66200	49300	2.55
215;HA2315	2-7/16	2.9528	5.1181	1.7323	1.1811	2.874	0.591	3.858	0.339			
215;HE2315	2-1/2											